LSLV0008G100-4EOFN

Технически данни за инвертора

Параметър	Нормално натоварване (ND)	Тежко натоварване (HD)
Мощност на двигателя	1.5 kW	0.75 kW
Номинален изходен ток	3.1 A	2.5 A
Претоварване за 60 s	120%	150%
Модел	LSLV0008G100-4EOFN	
Захранване	3 × 380-480 V AC, 50/60 Hz	
Изход	Трифазен, с регулируеми честота и напрежение	
Изходна честота	0-400 Hz; допустимият диапазон зависи от режима на управление и двигателя	
Защита на корпуса	IP20	
Размери H3 × W1 × D1	164 × 86.2 × 131.5 mm	
Монтажни размери W2 / H2	76.2 / 154 mm; отвори Ø4.5 mm	
Комуникация	RS485 / Modbus RTU	

Документация на производителя - LS Electric

LSLV0008G100-4EOFN

Technical product data

Parameter	Normal Duty (ND)	Heavy Duty (HD)
Motor power	1.5 kW	0.75 kW
Rated output current	3.1 A	2.5 A
Overload for 60 s	120%	150%
Model	LSLV0008G100-4EOFN	
Input supply	3 × 380-480 V AC, 50/60 Hz	
Output	Three-phase, variable frequency and voltage	
Output frequency	0-400 Hz; usable range depends on the control method and motor	
Enclosure protection	IP20	
Dimensions H3 × W1 × D1	164 × 86.2 × 131.5 mm	
Mounting dimensions W2 / H2	76.2 / 154 mm; Ø4.5 mm holes	
Communication	RS485 / Modbus RTU	