SV0075iS7-4

Технически данни за инвертора

Параметър	Нормално натоварване (ND)	Тежко натоварване (HD)
Мощност на двигателя	11 kW	7.5 kW
Номинален изходен ток	24 A	16 A
Претоварване за 60 s	110%	150%
Модел	SV0075iS7-4	
Захранване	3 × 380-480 V AC, 50/60 Hz	
Изход	Трифазен, с регулируеми честота и напрежение	
Изходна честота	0-400 Hz; допустимият диапазон зависи от режима на управление и двигателя	

Посочените ND номинали важат само с DC дросел (DCR). Без него се използват HD номиналите. Проверете комплектовката.

Документация на производителя - LS Electric

SV0075iS7-4

Technical product data

Parameter	Normal Duty (ND)	Heavy Duty (HD)
Motor power	11 kW	7.5 kW
Rated output current	24 A	16 A
Overload for 60 s	110%	150%
Model	SV0075iS7-4	
Input supply	3 × 380-480 V AC, 50/60 Hz	
Output	Three-phase, variable frequency and voltage	
Output frequency	0-400 Hz; usable range depends on the control method and motor	

ND ratings apply only with the DC reactor (DCR). Use the HD ratings without the reactor. Verify the supplied configuration.