# SV0022iS7-4

## Технически данни за инвертора

| Параметър | Нормално натоварване (ND) | Тежко натоварване (HD) |
|---|---|---|
| **Мощност на двигателя** | 3.7 kW | 2.2 kW |
| **Номинален изходен ток** | 8 A | 6 A |
| **Претоварване за 60 s** | 110% | 150% |
| **Модел** | SV0022iS7-4 | |
| **Захранване** | 3 × 380-480 V AC, 50/60 Hz | |
| **Изход** | Трифазен, с регулируеми честота и напрежение | |
| **Изходна честота** | 0-400 Hz; допустимият диапазон зависи от режима на управление и двигателя | |

Посочените ND номинали важат само с DC дросел (DCR). Без него се използват HD номиналите. Проверете комплектовката.

Документация на производителя - LS Electric

# SV0022iS7-4

## Technical product data

| Parameter | Normal Duty (ND) | Heavy Duty (HD) |
|---|---|---|
| **Motor power** | 3.7 kW | 2.2 kW |
| **Rated output current** | 8 A | 6 A |
| **Overload for 60 s** | 110% | 150% |
| **Model** | SV0022iS7-4 | |
| **Input supply** | 3 × 380-480 V AC, 50/60 Hz | |
| **Output** | Three-phase, variable frequency and voltage | |
| **Output frequency** | 0-400 Hz; usable range depends on the control method and motor | |

ND ratings apply only with the DC reactor (DCR). Use the HD ratings without the reactor. Verify the supplied configuration.